

**PRODUK**

		4/0.5 mm	4/0.3 mm
Klasifikasi	ASTM F1700	Kelas III / Tipe B	Kelas III / Tipe B
Aplikasi	EN ISO 10874	23/33	23/31
Instalasi	-	Sistem klik / Floating	Sistem klik / Floating
Garansi	Light Commercial	7 Tahun	5 Tahun

**SPESIFIKASI**

Tebal SPC	ISO 24346	4 mm	4 mm
Tebal Wear Layer	ISO 24340	0.5 mm	0.3 mm
Ukuran SPC (Tipe Wood)	ISO 24341	Panjang : 1220 mm Lebar : 180 mm	Panjang : 1220 mm Lebar : 180 mm
Ukuran SPC (Tipe Stone)	ISO 24341	Panjang : 610 mm Lebar : 305 mm	Panjang : 610 mm Lebar : 305 mm
Berat SPC	EN 430	8.25 kg/m <sup>2</sup>	8.25 kg/m <sup>2</sup>
Straightness/Squareness	ISO 24342	≤ 0,25 mm	≤ 0,25 mm
Edge profile	-	Standard dengan sistem klik	Standard dengan sistem klik


**PROPERTIES PRODUK**

Ketahanan Terhadap Abrasi	EN 660 : part-1	Grup T : ≤0,08 mm
Indentasi Sisa	ISO 24343-1	≤0.10 mm
Ketahanan Terhadap Kimia	EN 438	Grade 5
Ketahanan Terhadap Api	EN 13501 / ISO 9239-1	Kelas Bfl-s1(B1)
Stabilitas Dimensi	ISO 23999	≤0,12%
Color Fastness	ISO 105-B02:1994	≥Grade 6
Ketahanan Terhadap Air	EN 317	0% Swelling
Slip Resistance	AS 4586 / DIN 51130	R10
Emisi Formaldehida	EN 717-1	E1
Kandungan Phtalate	CPSC-CH-C1001-09.3	Tidak terdeteksi (Bebas phtalate)
Curving	ISO 23999	≤1,2mm
Peel Resistance	ISO 24345	≥50N/5cm
Locking strength	ISO 24344	≥120N/5cm
Castor Chair	ISO 4918	Tipe W : Setelah 25.000 siklus, tidak ada delaminasi yang terjadi. Tidak ada kerusakan pada permukaan selain sedikit perubahan tampilan

**KEMASAN**

Jumlah per box	Tipe Stone	14 Pcs
	Tipe Wood	12 Pcs
Area per box	Tipe Stone	2.60 m <sup>2</sup>
	Tipe Wood	2.63 m <sup>2</sup>

**METODE INSTALASI**



Brick



Ashlar



Stagger



Slip Resistant



Fire Resistant



Ecological



Abrasion Resistant



Chemical Resistant




Silent



Impact Resistant



Click System



**ALVERA**  
BEYOND THE ORDINARY



Contact Us

Alvera.Flooring

@alvera.flooring

www.alvera.co.id